



CITOKETT II™

HIGH PERFORMANCE OIL-BASED INK DEDICATED FOR FLATBED AND SEMIROTARY LETTERPRESS PRINTING

CITOKETT II™ has:

- Very good colour strength
- Good drying properties
- Very good printability
- Very good press stability
- Good adhesion to paper
- Unique characteristics for flatbed and semirotary printing

CITOKETT II™

is designed to be used in flatbed- and semirotary letterpress presses provided ink is dried with hot air or IR dryers in combination with air stream blowing on web

Suitable for a wide variety of applications:

- Self adhesive labels (coated & uncoated papers and cast coated papers)

Properties

- Excellent printability and press stability in flatbed letterpress
- Good drying properties
- Enhanced colour consistency and excellent mileage

Benefits

- Consistent high print quality throughout press run
- Improved productivity
- Improved print result and profitability

LETTERPRESS

Availability

- A range of Pantone® basic colours

The information contained in this brief product presentation is based on the long experience of Flint Group Narrow Web and on internal standardised tests. It is not to be interpreted as a warranty or guarantee in any form as conditions beyond our control can affect the quality of the printing. If there is any doubt, the user should always make every effort to ensure that the products used are appropriate for the purpose.

- very suitable
- suitable
- usable
- not suitable

CITOKETT II™	
Printing speed	Up to 30 m/min
Mileage* g/m ²	
Pantone	1,8 - 2,0
Solids	1,8 - 2,5
Printability	
Process	•••
Solids	•••
Material suitability	
Paper	•••
TC thermal papers	-
TC filmic substrates	•
Filmic substrates	-
Resistance properties	
Chemical	-
Water	-
Solvent	-
Combination printing	
UV screen	-
UV flexo	-
UV offset	-
UV letterpress	-
Water-based flexo	-
UV flexo varnish	-
Variable info printing	
Thermal overprinting	-
Thermal transfer	•
Hot foil	•
Cold foil radical	-
Laser overprinting	•
Ink jet overprinting	•
Lamination with	
Radical adhesive	-
Cationic adhesive	-

*Amount of ink in g/m² needed to obtain process density or match Pantone® shade.

For more details on Citokett II™,
call your nearest Flint Group Narrow Web office or dealer.



Flint Group Narrow Web

P.O. Box 1003, SE-231 25 Trelleborg, Sweden
Phone +46 410 59 200, Fax +46 410 59 397
www.narrowweb.flintgrp.com