



UV ADHESIVES

AN ENVIRONMENTALLY FRIENDLY RANGE OF HIGH PERFORMANCE, UV CURABLE LAMINATING ADHESIVES WITH:

- Good laminating adhesion
- Suitability for use with many substrates
- Capability to be used with many different ink technologies
- High cure speed

The UV ADHESIVE range can be used for paper to film and film to film constructions:

- Paper overlaminated with PE
- Paper overlaminated with PP
- Paper overlaminated with PET
- PE overlaminated with PP
- PE overlaminated with PE
- PP overlaminated with PP
- Foil overlaminated with PP
- Foil overlaminated with PE

The UV adhesive range can be used in combination with all Flint Group Narrow Web technologies. It is a VOC free alternative to solvent-based adhesives.

Properties

- High initial bond
- VOC free
- Press ready
- One component

Benefits

- No waiting for post curing
- Environmentally friendly
- Easy to handle
- Easy to handle

VARNISHES, ADHESIVES & PRIMERS

PRODUCT	DESCRIPTION	RECOMMENDED FILM WEIGHT
UVH01001	UV FLEXO GENERAL PURPOSE	4 - 6 g/m ²
UVC00100	UV FLEXO, CATIONIC	4 - 6 g/m ²

The information contained in this brief product presentation is based on the long experience of Flint Group Narrow Web and on internal standardised tests. It is not to be interpreted as a warranty or guarantee in any form as conditions beyond our control can affect the quality of the printing. If there is any doubt, the user should always make every effort to ensure that the products used are appropriate for the purpose.



For more details on UV ADHESIVES,
call your nearest Flint Group Narrow Web office or dealer.

Flint Group Narrow Web

Flint Group Narrow Web, 15500 28th Avenue North, Plymouth, MN 55447, USA
Phone (763) 559 5911, Toll Free in the U.S. (800) 328 7838, Fax (763) 559 0243
www.narrowweb.flintgrp.com