



UV ADHESIVES

AN ENVIRONMENTALLY FRIENDLY RANGE OF HIGH PERFORMANCE, UV CURABLE LAMINATING ADHESIVES WITH:

- Good laminating adhesion
- Suitability for use with many substrates
- Capability to be used with many different ink technologies
- High cure speed

The UV ADHESIVE range can be used for paper to film and film to film constructions:

- Paper overlaminated with PE
- Paper overlaminated with PP
- Paper overlaminated with PET
- PE overlaminated with PP
- PE overlaminated with PE
- PP overlaminated with PP
- Foil overlaminated with PP
- Foil overlaminated with PE

The UV adhesive range can be used in combination with all Flint Group Narrow Web technologies. It is a VOC free alternative to solvent-based adhesives.

Properties

- High initial bond
- VOC free
- Press ready
- One component

Benefits

- No waiting for post curing
- Environmentally friendly
- Easy to handle
- Easy to handle

VARNISHES, ADHESIVES & PRIMERS

PRODUCT	DESCRIPTION	RECOMMENDED FILM WEIGHT
UVH01001	UV FLEXO GENERAL PURPOSE	3 - 6 g/m ²
UVX00222	UV FLEXO GENERAL PURPOSE	3 - 6 g/m ²

The information contained in this brief product presentation is based on the long experience of Flint Group Narrow Web and on internal standardised tests. It is not to be interpreted as a warranty or guarantee in any form as conditions beyond our control can affect the quality of the printing. If there is any doubt, the user should always make every effort to ensure that the products used are appropriate for the purpose.



For more details on UV ADHESIVES,
call your nearest Flint Group Narrow Web office or dealer.

Flint Group Narrow Web

P.O. Box 1003, SE-231 25 Trelleborg, Sweden
Phone +46 410 59 200, Fax +46 410 59 397
www.narrowweb.flintgrp.com